

INCU-SHAKER Series

Exceptional temperature uniformity Compact, bench-top design (Mini, just 11" wide) Exchange flask clamps in one second with the new MAGiC CLAMP™ magnetic system



INCU-SHAKER IOL

125

- 100

- 7:



/////





Incu-Shaker 10L (H1010) H1010-P-MF







INCU-SHAKER"

The new Incu-Shaker™ series of shaking incubators provide digitally regulated temperature with precisely controlled, circular (orbital) mixing, optimized for the culture of a wide variety of cell types.

The Incu-Shaker Mini is the most compact shaking incubator in its class. Despite the remarkably small footprint, a large 11.5 x 9.5 in. work space accepts several platforms for use with a variety of flasks, tubes and other common vessels.

With similar features to the Incu-Shaker Mini, the Incu-Shaker 10L is equipped with a large 18 x 18 inch platform for high capacity applications. (See Chart for a complete listing of the maximum flask capacity.)

The standard platform (included with both models) features a non-slip, rubber coated surface, ideal for tissue culture flasks. Petri dishes and staining travs. Convenient MAGic Clamp[™] platforms, flask clamps and tube racks are also available for use with Erlenmeyer flasks and test tubes. This unique, magnetic attachment method is the easiest way to instantly change between flask clamps of different sizes. Each clamp utilizes a powerful (patent pending) magnetic base to securely attach the clamp to the shaking platform without the use of screws, bolts or tools.

Temperature, shaking speed and run time are displayed on the large LED control panel located on the front of the unit. The integral microprocessor includes a constant monitoring system that verifies and maintains accuracy through the duration of the program. Sophisticated over-temperature and over-speed controls ensure long life, safety and sample integrity.

Technical Data:

Temperature Range: Temperature Uniformity Temperature Accuracy: Shaking Speed Range: Shaking Orbit: Platform Dimensions: **Incu-Shaker Mini** Incu-Shaker 10L Exterior Dimensions: Incu-Shaker Mini Incu-Shaker 10L Weight: Incu-Shaker Mini Incu-Shaker 10L **Electrical:**

Ambient +5 to 60°C (Increments of 0.1°C) +/- 0.25 % +/-0.1% 30 to 300rpm (Increments of 1rpm) 19mm (3/4")

9.5 x 11.5 in. / 23.5 x 29.2 cm 17.8 x 17.8 / 45 x 45 cm

11 x 15.7 x 10.5 in. / 28 x 40 x 27 cm 20 x 26 x 19 in. / 51 x 65 x 47 cm

25 lbs. / 11.5 kg 120 lbs / 55 kg 120 or 230V. 50-60Hz

380 388 0000 000 Only 11" wide Incu-Shaker Mini

(H1000-M)

unu.



Ordering Information

H1000-M* H1010*

H1010-MR

H1000-P-MP

H1010-P-MP H1000-P-SP

H1010-P-SP

H1010-SH

Incu-Shaker Mini, includes standard rubber mat platform, 115V Incu-Shaker 10L, includes standard rubber mat platform, 115V *To order an item in 230V, add (-E) to item number.

Optional Platforms and Shelves H1000-MR

MAGic Clamp universal platform, for Incu-Shaker Mini (9.5x11.5") MAGic Clamp universal platform, for Incu-Shaker 10L (18x18") Microplate platform, 4 position for Incu-Shaker Mini Microplate platform, 6 position for Incu-Shaker 10L Spring rack platform, holds uncommon vessels for Incu-Shaker Mini Spring rack platform, holds uncommon vessels for Incu-Shaker 10L Optional Shelf, for Petri Dishes, microplates, trays, etc. (14 x 5.5") for Incu-Shaker 10L (max. 3)

Flask & Tube Rack Accessories for MAGic Clamp Platforms

H1000-MR-50 H1000-MR-125 H1000-MR-250 H1000-MR-500 H1000-MR-1000 H1000-MR-2000 H1000-MR-MP H1000-MR-1550

Flask Clamp, 50ml (H1000-MR: max. 20 / H1010-MR: max. 49) Flask Clamp, 125ml (H100-MR: max. 12 / H1010-MR: max. 35) Flask Clamp, 250ml (H1000-MR: max. 8 / H1010-MR: max. 25) Flask Clamp, 500ml (H1000-MR: max. 5 / H1010-MR: max. 16) Flask Clamp, 1000ml (H1010-MR: max. 9) Flask Clamp, 2000ml (H1010-MR: max. 5) Microplate Clamp, (H1000-MR: max. 4 / H1010-MR: max. 6) Tube Rack, 12x50 & 21x15 ml tubes (H1000-MR: max.1 / H1010-MR: max.4) Tube Rack, 32x15 tubes (H1000-MR: max. 2 / H1010-MR: max. 8) Tube Rack, 15x50 tubes (H1000-MR: max. 2 / H1010-MR: max. 8) Bottle Rack, 4x500/600ml conical bottles (H1000-MR: max. 1 / H1010-MR: max. 2)

PO Box 709 Edison, NJ 08817 TEL: 908-769-5555 Fax: 908-222-1864 Web: www.BenchmarkScientific.com Email: Info@BenchmarkScientific.com